




Product Specification Sheet

Isolating Ball Valve



Compact, screwdriver actuated, chrome plated brass isolating ball valve.

Product Features and Benefits

- **Compact, high quality** valve gives durability and secure isolation when activated.
- **Nickel plated** versions available for even **longer life**.
- Chrome plated brass ball, encapsulated between two high grade NBR seals, gives **smooth operation and 100% reliability**.
- BS 864 compression connections for **ease of assembly**.

Isolating Ball Valve

Description

Manufactured from OT58 brass this isolating valve is compact in design and easy to install. It has a chromium plated ball, also made from OT58 brass which is encapsulated between two NBR Elastomer seals. It is available either nickel plated or as self coloured brass and comes in both 15mm and 22mm sizes.


Product Range

BVAL 200 001: 15mm Isolating Ball Valve - Brass
BVAL 200 002: 15mm Isolating Ball Valve - Nickel plated
BVAL 200 003: 22mm Isolating Ball Valve - Brass
BVAL 200 004: 22mm Isolating Ball Valve - Nickel plated

Materials

Body: Stamped OT58 Brass
(Also available in a nickel-plated finish)
Ball: OT58 brass – chromium plated
Spindle: OT58 brass
Seals: NBR Elastomer

Dimensions



	A	B	Ø Bore	Connection
BVAL 200 001	55	23	8	15mm comp.
BVAL 200 002	55	23	8	15mm comp.
BVAL 200 003	72	32	12	22mm comp.
BVAL 200 004	72	32	12	22mm comp.

All dimensions in mm unless stated

Specifications

Test Pressure: 15 bar
Working Pressure: 10 bar Max.
Working Temperature: 85°C Max.

How to Specify

A compact, high quality isolating ball valve with compression connections, in either brass or nickel plated finish (include correct product range code).

Guarantee

All Reliance® products undergo strict performance tests prior to despatch, and are guaranteed against faulty materials and workmanship for one year from date of purchase. This is in addition to any statutory rights.

Contacts:	Sales Enquiries	Technical Support
Telephone:	+44 (0)1386 712400	+44 (0)1386 47148
Fax:	+44 (0)1386 47028	+44 (0)1386 422217
E-Mail:	sales@rwc.co.uk	technical@rwc.co.uk



Reliance Water Controls®
Worcester Road, Evesham, Worcestershire, WR11 4RA, UK
Tel: +44 (0)1386 47148 Fax: +44 (0)1386 47028 www.rwc.co.uk

