



## SHARKBITE® FILLING LOOP WITH STREET ENDS

SB2315ST

Filling loop with street ends, 15mm, pack quantity: 1

### OVERVIEW

Filling loop with street ends suitable for direct connection to SharkBite metal push-fit fittings.



WATER CONTROLS FOR A MODERN WORLD

RELIANCE

TEMPERATURE CONTROL

FLOW CONTROL

HEATING SYSTEM COMPONENTS

WASHROOM SYSTEMS

HEATING & COOLING DISTRIBUTION SYSTEMS

PLUMBING SYSTEMS

# SHARBITE® FILLING LOOP WITH STREET ENDS

## FEATURES AND BENEFITS

- Street ends to be used in conjunction with SharkBite fittings
- 1/8" BSP test port on isolating double check valve
- Suitable for Class 3 contamination risks
- Ball valve with lever for easy operation
- Comes with metal watertight blanking cap, for additional security
- Thumb-grip nuts on hose to allow quick connection/disconnection to mains supply
- Conforms to Water Supply Regulations (1999) section 8 Paragraph R24.2

## STANDARDS AND APPROVALS

- WRAS Approved

## HOW TO SPECIFY

WRAS 1999 compliant filling loop made up of: isolating ball valve and combined isolator double check valve with test port (1/8"), flexible hose with street ends for connection to push-fit fittings. (Include correct product code).

## SPECIFICATIONS

Maximum pressure: 6.0 bar  
 Maximum operating temperature: 65°C

## MATERIALS

Body:	DZR brass
Check cartridges:	Acetal polymer
	NBR elastomer seals
	Stainless steel spring
Hose tubing:	EPDM elastomer
Hose braiding:	Stainless steel 7 strand
Hose end fittings:	Nickel plated brass
Ball valve body:	Nickel plated brass
Ball valve ball:	Chrome plated brass
Ball valve seals:	PTFE

## DIMENSIONS

All dimensions in mm unless otherwise stated.

