



SHARKBITE® 90° ELBOW

SB0210	90° Elbow, 10mm, Pack Quantity: 5
SB0215	90° Elbow, 15mm, Pack Quantity: 10
SB0222	90° Elbow, 22mm, Pack Quantity: 5
SB0228	90° Elbow, 28mm, Pack Quantity: 5
SB0235E	90° Elbow, 35mm, Pack Quantity: 1
SB0242E	90° Elbow, 42mm, Pack Quantity: 1
SB0254E	90° Elbow, 54mm, Pack Quantity: 1

OVERVIEW

The SharkBite range of slimline metal push-fit plumbing fittings provide a fast, secure and heat-free pipework connection which is suitable for all domestic and commercial applications. The fittings are compatible with all types of commonly used metal and plastic pipe: copper, PEX, carbon steel and polybutylene. They can be easily disconnected and are immediately re-usable. This selection of elbows connects pipe at a 90 degree angle with SharkBite's quick and simple cut – push – done operation.



WATER CONTROLS FOR A MODERN WORLD

RELIANCE

TEMPERATURE
CONTROL

FLOW
CONTROL

HEATING SYSTEM
COMPONENTS

WASHROOM
SYSTEMS

HEATING & COOLING
DISTRIBUTION SYSTEMS

PLUMBING
SYSTEMS

SHARKBITE® 90° ELBOW

WORKING PRESSURES AND TEMPERATURES

Size	Pipe	Pressure/Temperature			
		12 Bar / -20°C	12 Bar / 20°C	6 Bar / 65°C	6 Bar / 95°C
15mm	PEX or PB	12 Bar / -20°C	12 Bar / 20°C	6 Bar / 65°C	6 Bar / 95°C
	Copper	20 Bar / -24°C	16 Bar / 30°C	10 Bar / 65°C	6 Bar / 95°C
10mm	PEX or PB	12 Bar / -20°C	12 Bar / 20°C	6 Bar / 65°C	6 Bar / 95°C
	Copper/Carbon Steel	20 Bar / -24°C	20 Bar / 30°C	16 Bar / 65°C	10 Bar / 120°C
22mm	PEX or PB	12 Bar / -20°C	12 Bar / 20°C	6 Bar / 65°C	6 Bar / 95°C
	Copper/Carbon Steel	20 Bar / -24°C	20 Bar / 30°C	16 Bar / 65°C	10 Bar / 120°C
28mm	PEX or PB	12 Bar / -20°C	12 Bar / 20°C	6 Bar / 65°C	6 Bar / 95°C
	Copper/Carbon Steel	20 Bar / -24°C	20 Bar / 30°C	16 Bar / 65°C	10 Bar / 120°C
35mm	Copper/PEX/Carbon Steel	16 Bar / -24°C	16 Bar / 30°C	10 Bar / 65°C	6 Bar / 95°C
42mm	Copper/PEX/Carbon Steel	16 Bar / -24°C	16 Bar / 30°C	10 Bar / 65°C	6 Bar / 95°C
54mm	Copper/PEX/Carbon Steel	16 Bar / -24°C	16 Bar / 30°C	10 Bar / 65°C	6 Bar / 95°C

FEATURES AND BENEFITS

- Quick and easy to install in both wet or dry conditions
- Heat/flux free installation, ideal for use where flame jointing is not permitted
- No expensive tools required
- Quick and easy to demount
- Instantly reusable
- Versatile: same fitting can connect all types of commonly used metal and plastic pipe, in any combination
- Slim, compact design and fully rotatable: ideal for use in confined spaces or on exposed pipework
- Electrically continuous (when used with copper or carbon steel pipe)

STANDARDS AND APPROVALS

- WRAS Approved

PIPE COMPATABILITY

COPPER: Copper pipe manufactured in accordance with BS EN 1057 in sizes 10mm to 54mm. If 10mm annealed Copper pipe is being used, it must be re-calibrated in accordance with Table 4 R250 tolerances in the above standard and a Copper liner installed into the pipe prior to assembly.

PEX: SharkBite cross linked Polyethylene (PEX) manufactured to BS 7291: Part 3 in sizes 10mm to 54mm utilising the specific manufacturer's pipe liner.

POLYBUTYLENE: Polybutylene (PB) manufactured to BS 7291: Part 2 when utilising the specific manufacturer's liner.

CARBON PIPE: Carbon Steel pipe manufactured to EN 10305-2

ELECTRICAL CONTINUITY: SharkBite fittings are TRaC certified to provide electrical continuity when used with Copper or Carbon Steel pipe with the exception of 10mm fittings.

MATERIALS

- Body: DZR Brass
- O Ring: Ethylene Polypropylene Diene Monomer (EPDM)
- 15mm Cartridge: 304 Stainless Steel
- Grab Ring: 316 Stainless Steel
- Disconnecting Ring: Acetal Copolymer
- Alignment Ring: Nylon 6

GUARANTEE


As a result of the rigorous manufacturing and quality controls and also internal long term test results, all SharkBite fittings are guaranteed against defects in materials or manufacturing for a period of 25 years from the date of purchase.

ACCESSORIES

- SB2910: 10mm Depth Marker/Disconnecting Clip
- SB2915: 15mm Depth Marker/Disconnecting Clip
- SB2922: 22mm Depth Marker/Disconnecting Clip
- SB2928: 28mm Depth Marker/Disconnecting Clip
- SB2910-28: 10mm–28mm Depth Marker/ Disconnecting Clip Set
- SB3010: 10mm Disconnecting Tongs
- SB3015: 15mm Disconnecting Tongs
- SB3022: 22mm Disconnecting Tongs
- SB3028: 28mm Disconnecting Tongs
- SB2935: 35mm Disconnecting Clip
- SB2942: 42mm Disconnecting Clip
- SB2954: 54mm Disconnecting Clip
- SB2935-54: 35-54mm Depth Marker

DIMENSIONS

All dimensions in mm unless otherwise stated.



Size	Code	A	Za
10mm	SB0210	31mm	8mm
15mm	SB0215	34mm	9mm
22mm	SB0222	43mm	13mm
28mm	SB0228	46mm	14mm
35mm	SB0235E	70mm	19mm
42mm	SB0242E	80mm	23mm
54mm	SB0254E	93mm	29mm